



Great Sound for the Great Outdoors

All-Weather Series Surface Mount Speakers

Take your favorite music outdoors with Episode. These all-weather speakers can handle the elements and fit seamlessly into any space – all while delivering exceptional sound.



Awesome Aesthetics

Soft edges and various color and size options help Episode speakers blend into anything from a backyard to a backyard bistro, while a compact form factor helps them fit under an eave or awning if you so choose.

Designed for Durability

From rain to wind, these speakers can handle it all. A true all-weather product, they feature aluminum grilles and brackets, a UV-treated, mineral-filled polypropylene cabinet, and stainless steel bolts. Beyond an ability to withstand the elements, these speakers can safely operate in temperatures between -4 and 140 degrees Fahrenheit.

Exceptional Outdoor Sound

Thanks to premium components – like a polypropylene woofer and titanium dome tweeter – Episode speakers are optimized for outdoor listening. Perfect for everything from easy listening on a weeknight to a party on the weekend.

All-Weather Series Surface Mount Speakers

	8 Ohm				70-Volt		
	ES-500-AW-8 (Black or White)	ES-500-AW-6 (Black or White)	ES-500-AW-4 (Black or White)	ES-500-AW-DVC-6 (Black or White)	ECS-500- AW70V-8 (Black or White)	ECS-500- AW70V-6 (Black or White)	ECS-500- AW70V-4 (Black or White)
Sold As	Pair	Pair	Pair	Each	Each	Each	Each
Dimensions (W x H x D)	Without Bracket: 9.1" x 12.6" x 8.6" With Bracket: 9.13" x 12.6" x 9.1"	Without Bracket: 7.5" x 11.1" x 7.2" With Bracket: 7.5" x 11.1" x 7.7"	Without Bracket: 6.5" x 9.7" x 7.2" With Bracket: 6.5" x 9.7" x 6.6"	Without Bracket: 7.5" x 11.1" x 7.2" With Bracket: 7.5" x 11.1" x 7.7"	Without Bracket: 9.1" x 12.6" x 8.6" With Bracket: 9.1" x 12.6" x 9.1"	Without Bracket: 7.5" x 11.1" x 7.2" With Bracket: 7.5" x 11.1" x 7.7"	Without Bracket: 7.2" x 9.7" x 6.6" With Bracket: 6.5" x 9.7" x 6.6"
Weight	8.9 lb	7.3 lb	6.45 lb	7.54 lb	10.7 lb	8.9 lb	7.39 lb
Connectors	Gold Plated Push Terminal	Gold Plated Push Terminal	Gold Plated Push Terminal	Gold Plated Push Terminal	Gold Plated Push Terminal	Gold Plated Push Terminal	Gold Plated Push Terminal
Line Voltage	n/a	n/a	n/a	n/a	70.7V / 100V	70.7V / 100V	70.7V / 100V
Transformer Tap Settings	n/a	n/a	n/a	n/a	7.5W (70V only), 15W, 30W, 60W	7.5W (70V only), 15W, 30W, 60W	3.75W (70V only), 7.5W, 15W, 30W
Nominal Impedance	8 Ohm	8 Ohm	8 Ohm	8 Ohm	n/a	n/a	n/a
Frequency Response	60Hz- 20Khz	65Hz- 20Khz	70Hz- 20Khz	65Hz- 20Khz	60Hz- 20Khz	65Hz- 20Khz	70Hz- 20Khz
Crossover Frequency	2.0kHz	2.2Khz	2.5Khz	2.5Khz	2.0kHz	2.2Khz	2.5Khz
Power Peak	350W	325W	300W	165W per Channel	n/a	n/a	n/a
Sensitivity	90dB	88dB	87dB	89dB	90dB	88dB	87dB
Woofers	8" Polypropylene cone woofer with vacuum-deposited titanium	6" Polypropylene cone woofer with vacuum-deposited titanium	5" Polypropylene cone woofer with vacuum-deposited titanium	6" Polypropylene cone woofer with vacuum-deposited titanium	8" Polypropylene cone woofer with vacuum-deposited titanium	6" Polypropylene cone woofer with vacuum-deposited titanium	5" Polypropylene cone woofer with vacuum-deposited titanium
Tweeter	1" Pure titanium dome tweeter	1" Pure titanium dome tweeter	3/4" Pure titanium dome tweeter	Dual 3/4" Pure titanium dome tweeters	1" Pure titanium dome tweeter	1" Pure titanium dome tweeter	3/4" Pure titanium dome tweeter