

Features

Compact Flat Design.

Triad AcoustiPerf metal grill available in three designs: Narrow, Wide, and Frameless.

Fully engineered, Premium MDF enclosure.

Acoustic Suspension.

2-way design.

Cabinet Specifications

Height: 19" /48.2cm

Width: 10 3/4" /27.3cm

Depth: 5 15/16" /15cm

Hole Cut Out - Height: 19 1/8" /48.5cm

Hole Cut Out - Width: 10 7/8" /27.6cm

Frameless Grill Dimensions:

W: 12 1/4" x H: 20 1/2" /W: 31cm x H: 52cm

Narrow Grill Dimensions:

W: 11 7/16" x H: 19 11/16" /W: 29.1cm x H: 50cm

Wide Grill Dimensions:

W: 12" x H: 20 5/16" /W: 30.6cm x H: 51.6cm

Product Weight: 25lbs /11.3kg

Shipping Weight: 28lbs /12.7kg

NCB Size: C

Performance Specifications

Recommended Amp Power:

50 - 150 watts

Impedance: 4 ohms

Sensitivity (db 1watt/1meter): 87

Anechoic Frequency Response:

50 Hz - 20 kHz

Tweeter Type: Fabric dome

Tweeter Size: (1) 1" /25mm

Woofers Type: Proprietary paper/fiber blend

Woofers Size: (1) 6-1/4" 16cm

Finishes

Triad's Basic & Custom Finishes are available for this product. The standard finish for this product is White paint. For any other colors, please refer to Triad's Custom Match Finish program for this product.



INWALL GOLD/6 MINIMONITOR

The InWall Gold/6 MiniMonitor is appropriate for a wide variety of custom applications where a compact full-range upscale solution is needed. It features a single 6.25" Scan-Speak low-loss, linear suspension, sliced cone woofer/midrange driver, and a 1" fabric dome tweeter. Premium components are used throughout. The InWall, InCeiling, and InRoom versions of the Gold MiniMonitor were designed to deliver true audiophile reproduction in a compact design. Each model can be used for high-end two-channel systems as well as with subwoofers in premium home theater applications. Bass response is surprisingly deep and clean, and treble is delicate and detailed, yet effortless.

The InWall version features a fully engineered braced and damped enclosure like the InRoom version for accurate, predictable sound and freedom from bleeding into adjacent rooms when installed. A minimum of 6" of stud depth is required for installation. The InWall Gold/6 MiniMonitor Acoustiperf grill can be ordered in virtually any custom color to blend into any environment.

