MOBIUS3iB

FRONT-MOUNTING DEVELOPER SERIES PLASTER-OVER LOUDSPEAKER WITH INTEGRATED BACKBOX

DATASHEET Rev. 1.3 | 20-10-2023 | E&OE




Product Description

New to the Mobius range of fully-covered loudspeakers, the Mobius3iB offers a smaller footprint alternative to the Mobius5iB and Mobius7iB for use when there is limited stud/joist spacing or to supplement full-size speakers within a large project, providing a cost-effective solution for lesser rooms such as spare bedrooms or hallways. Rendered invisible behind a 2mm skim of plaster, the Mobius3iB uses the same OptiDriver and OptiDamping technology found on the flagship Mobius7iB invisible loudspeakers. The Mobius3iB features an all-new integrated backbox which is sealed, acoustically tuned and provides protection throught the life of the speaker. The streamlined installation process automatically aligns the speaker to the correct depth, ultimately resulting in a faster, easier installation. Paired with a subwoofer the Mobius3iB can be used for medium-level, full-bandwidth music listening at a highly competitive price point.

Example Applications

Invisible audio installations with space limitations. Distributed audio and medium-level listening within residential properties such as MDU's. Cost-sensitive commercial background music applications.





Specifications

Mobuis3iB

| - I | |
|---|--|
| Nominal impedance | 4 Ohms |
| Power handling (100 hour continuous/peak) | 30W/60W |
| Sensitivity (@ 1m/2.83Vrms) | 85dB (with 2mm plaster/mud skim) |
| Frequency response | 87Hz - 19kHz (-6db) |
| Useable Frequency Range | 67Hz - 31kHz (-10db) |
| Dispersion angle | 180° x 180° at specified frequency range |
| Electrical connection | (14-16 AWG) |
| Dimensions (not including mounting tabs) | 402mm x 304mm x 77mm (1513/16" x 1115/16" x 31/16") |
| Product weight | 2.5Kg (5lbs 8oz) |
| Fixing requirements | All fixings provided |
| In-line protection unit | APUi30C, APU-RS8iC, APU-RS16iC or The Guardian Active Protection |
| Manufacturer limited residential warranty | 10 years |