

1x2 HDMI Signal Manager

Product code: 2.50.795



A versatile HDMI signal management tool offering video downscaling and audio downmixing. Useful in distributed video environments containing a range of differing display resolution capabilities. The downscaling function of the device can be used to always ensure optimal performance of each display. HDMI video scaler: Input supports 18Gbps, 4K, HDR, HDMI 2.0 and HDCP 2.2 content, downscalable to 4K/10G for use on HDMI 1.4 equipment, or 4K/18G to 1080p with matched frame rates. The two HDMI output ports act as follows: HDMI Output 1 = always passes through the unaltered original signal. HDMI Output 2 = can be set to pass through same as HDMI Output 1, or scale down to 4K/1080p @10G and can have downmixed 2ch stereo audio re embedded. Audio connectivity: 5.1 multi channel audio can also be downmixed to 2ch stereo via RCA or TOSLINK optical ports (or re embedded onto HDMI Output 2).

FEATURES

HDMI splitting, scaling and audio management features.
HDMI® 2.0 (a/b) HDCP 2.2 compliant
18Gbps data rate throughout
Supports all resolutions up to and inc. Ultra HD 4K 60 4:4:4
Supports all current High Dynamic Range (HDR) formats
Supports all current audio formats up to Dolby Atmos® and DTS:X®
2-year guarantee

SPECIFICATIONS

Form factor	Lightweight slender aluminium enclosure
Inputs / outputs	1 HDMI to 2 HDMI, 1 L/R RCA, 1 TOSLINK
Transmission tech.	Native HDMI
Video bandwidth	594MHz
ESD protection	± 8kV (air-gap discharge) ± 4kV (contact discharge)
Device / Package weight	125 / 1100 g
TX / RX Dimensions (W/D/H)	56 / 100 / 16mm
Power	Output: DC 5V/1A (US/EU standards, CE/FCC/UL certified)
Operating temperature	0°C ~ 40°C / 32°F ~ 104°F
Storage temperature	-20°C ~ 60°C / -4°F ~ 140°F
Relative humidity	20~90 % RH (non-condensing)
Power consumption	2W
Guarantee	2-year guarantee